



Great Plains Industries, Inc.
 5252 East 36th Street North
 Wichita, KS 67220-3205
 Telephone: 316-686-7361
 Toll Free (USA & Canada): 800-835-0113
 Fax: 316-686-6746
 Sales Email: gpisales@gplains.com

01A31



Series		01A31
Design		Turbine
Housing		Aluminum
Fitting Size	Option 1	1 inch
Fitting Type	Option 1	NPT
	Option 2	ISO
Flow Range	GPM	3-30 GPM
	LPM	10-100 LPM
Accuracy		+ -5% of reading
Repeatability		+ -5%
Pressure Rating	PSIG	300 PSIG
	bar	21 bar
Operating Temperature Range	Fahrenheit	14 to 130°F
	Celsius	-10 to 54°C
Wetted Components	Housing	Aluminum
	Journal Bearings	Ceramic
	Shaft	Tungsten Carbide
	Rotor	Nylon 6-6
	Rings	316 SS
	Signal Generators	Ferrite (Ceramic Magnet)
Strainer Size		28 mesh
Maximum Flow	GPM	30 GPM
	LPM	100 LPM
Maximum Pressure Drop in 10:1 Range	PSIG	1.7 PSIG
	bar	.12 bar @ 100 LPM
Shipping Weight	lbs	2 lbs
	kg	0.9 kg
Approvals		Not Approved for Use with Aviation Fuel
Power Source		2 ea. AAA batteries
Electronic Features	Feature 1	2 Totals (1 Cumulative, 1 Batch)
	Feature 2	Permanent factory calibration for measuring gasoline, diesel or kerosene