



Sea-Lect® Check Valve

CV-2600A/2600B



CV-2600A - Aluminum

- Creates & maintains pump prime
- Doubles pump lift for Guzzler "2600" Series pumps
- Prevents fluid backflow
- Available in either aluminum or bronze
- Accommodates 1-1/4" - 2" hose


Performance

| | |
|-----------------------------------|---|
| Max Pressure | 20 psi (1.4 kg/cm ²) |
| Max Lift | 12 ft (3.7 m) |
| Pressure Drop (Cracking Pressure) | 2.7 x 10 ⁻² psi (0.75 in. of water) 1.9 x 10 ⁻³ kg/cm ² |
| Max Service Temp | 190°F (88°C) |

Available Ports

| | | | | |
|---------------------|----|-------|-------|------|
| | in | 1-1/4 | 1-1/2 | 2 |
| | cm | 3.18 | 3.81 | 5.08 |
| Hose (Smooth) | | | | S |
| NPT Female (Tapped) | • | | | |
| NPT Male (Threaded) | | • | | |

S Standard • Optional



CV-2600B - Bronze

Valve Options




Flapper — Steel plate reinforced. General purpose liquid transfer.


Materials

| | |
|------------------|--|
| Body * | Epoxy-coated Aluminum / Blue Bronze / Bronze |
| Valve * | Flapper: Buna-N |
| Fasteners | Stainless Steel |

* In contact with fluid



A



B

C

| | | |
|--------|---------|---------|
| | in | cm |
| A | 5-3/4 | 14.6 |
| B | 3 | 7.6 |
| C | 4 | 10.2 |
| Weight | 1.15 lb | 0.52 kg |

Sea-Lect® Check Valve CV-2600A / 2600B



Example: CV-2600A-1-9090

- Sea-Lect Check Valve
- Model style 2600A (Aluminum/Blue)
- Flapper Valve
- 2" Smooth Hose Connections

CV – 2600A – 1 – 90 90

| Sea-Lect Product | |
|------------------|------|
| Option | Code |
| Check Valve | CV |

| Family | |
|--------------------------------|-------|
| Option | Code |
| 2" Nominal Port Size, Aluminum | 2600A |
| 2" Nominal Port Size, Bronze | 2600B |

| Valve | |
|------------------|------|
| Option | Code |
| Flapper (Buna-N) | 1 |

| Option | Code | |
|---------------------|-------|--------|
| | Inlet | Outlet |
| 1-1/4" NPT Tapped | 71 | 71 |
| 1-1/2" NPT Threaded | 82 | 82 |
| 2" Smooth | 90 | 90 |