



Sea-Lect® Check Valve

CV-2600A/2600B



CV-2600A - Aluminum

- Creates & maintains pump prime
- Doubles pump lift for Guzzler "2600" Series pumps
- Prevents fluid backflow
- Available in either aluminum or bronze
- Accommodates 1-1/4" - 2" hose


Performance

Max Pressure	20 psi (1.4 kg/cm ²)
Max Lift	12 ft (3.7 m)
Pressure Drop (Cracking Pressure)	2.7 x 10 ⁻² psi (0.75 in. of water) 1.9 x 10 ⁻³ kg/cm ²
Max Service Temp	190°F (88°C)

Available Ports

	in	1-1/4	1-1/2	2
	cm	3.18	3.81	5.08
Hose (Smooth)				S
NPT Female (Tapped)	•			
NPT Male (Threaded)			•	

S Standard • Optional



CV-2600B - Bronze

Valve Options




Flapper — Steel plate reinforced. General purpose liquid transfer.


Materials

Body *	Epoxy-coated Aluminum / Blue Bronze / Bronze
Valve *	Flapper: Buna-N
Fasteners	Stainless Steel

* In contact with fluid



A



B

C

	in	cm
A	5-3/4	14.6
B	3	7.6
C	4	10.2
Weight	1.15 lb	0.52 kg

Sea-Lect® Check Valve CV-2600A / 2600B



Example: CV-2600A-1-9090

- Sea-Lect Check Valve
- Model style 2600A (Aluminum/Blue)
- Flapper Valve
- 2" Smooth Hose Connections

CV – 2600A – 1 – 90 90

Sea-Lect Product	
Option	Code
Check Valve	CV

Family	
Option	Code
2" Nominal Port Size, Aluminum	2600A
2" Nominal Port Size, Bronze	2600B

Valve	
Option	Code
Flapper (Buna-N)	1

Option	Code	
	Inlet	Outlet
1-1/4" NPT Tapped	71	71
1-1/2" NPT Threaded	82	82
2" Smooth	90	90