

# Par-Max marine freshwater delivery pumps

Designed to provide years of satisfactory service in applications both large and small

Xylem's Jabsco Par-Max pumps includes a range of flows and a variety of pressure settings to suit each individual need and preference.

	Par-Max 1	Par-Max 2	Par-Max 3	Par-Max HD3	Par-Max HD4	Par-Max HD5	Par-Max HD6
Open flow GPM (LPM)	1 (3.8)	2 (7.6)	3 (11)	3 (11)	4 (15)	5 (19)	6 (23)
Voltage options VDC	12	12, 24	12, 24	12	12, 24	12	12, 24
Pressure switch options PSI	35	35	40, 25	60, 40	60, 40 (25 EU only)	60, 40	60, 40
Quick Connect Strainer	Not included	 Inline 40 mesh	 Inline 40 mesh	 Inline 40 mesh	 Inline 40 mesh	 90° 40 mesh	 90° 40 mesh
Quick Connect Straight Hosebarb Fittings	 2 x 3/8" **	 2 x 1/2"	 2 x 1/2"	 2 x 1/2"	 2 x 1/2"	 2 x 1/2" 2 x 3/4"	 2 x 3/4"

\*\*Par-Max 1 also includes 2 x 3/8" to 1/2" adapter

## Key features:

- Co-molded diaphragm technology for long life and durability
- HD models feature heavy duty motors and cast aluminum lower housings which allow for long life, even at high pressures
- Efficient and quiet operation
- Integrated, sealed pressure switch for on-demand operation
- Self-priming allows for installation versatility
- Can run dry without damage
- Quick-connect ports for ease of installation, servicing, and maintenance
- Vibration dampening mounting feet
- Equipped with an integrated bypass module to reduce cycling and provide smoother flow

## Other available fittings & accessories:

### Accumulator tanks














Used to reduce pump cycling and allow for even smoother water flow. Variety of sizes and configurations available.

### Inlet water pressure regulator



Protects system from overpressurized city water.

## Port fittings

	Description	Compatible model lines	Consumer pack (2 unless noted)	Bulk 50 pack
	3/8" Straight hose barb	1 GPM	1877K-1122S	1877K-1129S-50
	1/2" Straight hose barb 3/4" Straight hose barb	2-5 GPM 2-5 GPM	1877K-2222S 1877K-3222S	1877K-2229S-50 1877K-3229S-50
	1/2" Elbow hose barb 3/4" Elbow hose barb	2-5 GPM 2-5 GPM	1877K-2222E 1877K-3222E	1877K-2229E-50 1877K-3229E-50
	1/2"-14 Straight NPS	2-5 GPM	1877K-2242S	1877K-2249S-50
	1/2"-14 Elbow NPS	2-5 GPM	1877K-2242E	1877K-2249E-50
	3/4" Straight garden hose thread	2-5 GPM	1877K-3211S (one per pack)	1877K-3219S-50
	3/4" Straight hose barb	6 GPM	1877K-3322S	1877K-3329S-50
	3/4" Elbow hose barb	6 GPM	1877K-3322E	1877K-3329E-50
	1/2"-14 Straight NPS	6 GPM	1877K-2342S	1877K-2349S-50
	1/2"-14 Elbow NPS	6 GPM	1877K-2342E	1877K-2349E-50
	3/4" Straight garden hose thread	6 GPM	1877K-3311S (one per pack)	1877K-3319S-50



Scan the QR code to access the product page for complete product details.