



| | | | | | | | |
|----------------|-----------|---|------------|--|----------|---------------------------------|------------------|
| Lid seal | 1 | 2 | Tätning | | | | 05-23-420 |
| Screw | 10 | 1 | Skruv UBS | | | | 05-04-124 |
| Screw | 9 | 6 | Skruv ULCS | | | MIS 08 | 05-04-171 |
| Screw | 8 | 1 | Skruv ULCS | | | Nr. 10-32 UNFX25 | 05-04-15 |
| Bush | 7 | 2 | Bussning | | | Nr. 8-32 UNCX8 | 05-13-110 |
| Gasket | 6 | 1 | Abtätning | | | Nr. 8-32 UNCX10 | 01-42391 |
| Impeller | 5 | 1 | Impeller | | | Unv. R12", inv. R3/8" | 08-1026.B |
| Shaft | 4 | 1 | Axel | | | | 01-42390 |
| Cam | 3 | 1 | Kam | | | | 01-42389 |
| Endcover | 2 | 1 | Lock | | | | 01-42388 |
| Body | 1 | 1 | Pumpphus | | | | 01-42387 |
| Detail nr | Antal | | Benämning | | Material | Dimension | Ann. el. rfm. nr |
| Tolerans | Tolerans | | Tolerans | | Blad | Godkänd | Smrt. rfm. |
| Arbetsnöd | Arbetsnöd | | Arbetsnöd | | Datum | 21.11.75 | Rfm. nr |
| | | | | | Sign. | JT | Sycklata nr |
| JOHNSON METALL | | | The | | | 10-32588-1, Type F4B-9 (FM3/8') | |
| ARBETSLAG | | | Benämning | | | Skala: 1:1 | |
| OREBRO | | | Benämning | | | Rm. nr | |
| | | | | | | 10-32588-1 | |

| | | | |
|-----|------------------------------------|----------|-------|
| R02 | Engelsk text tillkommit | 2.5.77 | OJ |
| 1 | Det nr 12. O-ring 05-06-500 utgått | 24.11.76 | OJ |
| | Mått införd | 21-1-75 | HZ |
| TM | Kontroll | Datum | Sign. |