A WILD COMPANY

ANSI Flanges

Create an ANSI flanged pump from an NPT ported pump using an ANSI Flange with a nipple.

These are standard ANSI Bronze flanges as used in hundreds of applications.

| Scot No. | Nominal Pipe Size NPT H | Flange Diameter A | 5 | Diameter of Bolt Circle D | Diameter of Bolt Holes E | Number of Bolts | Diameter of Bolts |
|-------------|----------------------------------|-------------------------|------|---------------------------------|--------------------------------|--------------------|----------------------|
| 189.001.471 | 1-1/2 | 5 | 7/16 | 3-7/8 | 5/8 | 4 | 1/2 |
| 189.001.472 | 2 | 6 | 1/2 | 4-3/4 | 3/4 | 4 | 5/8 |
| 189.001.473 | 2-1/2 | 7 | 9/16 | 5-1/2 | 3/4 | 4 | 5/8 |
| 189.001.474 | 3 | 7-1/2 | 5/8 | 6 | 3/4 | 4 | 5/8 |

ANSI Bronze Flange Dimensions 150 lb

Flanges are smooth, finished over the entire face and are provided with two concentric gasket retaining grooves inside the bolt holes.

Flange diameters and drilling templates of 150 lb Bronze flanges are the same as corresponding sizes of the ANSI 125 lb Cast Iron Flange Standard, ANSI B16.1, and the ANSI Class 150 Steel Flange Standard, ANSI B16.5.

