



WALBRO ENGINE MANAGEMENT

FRC-8 Reciprocating Fuel Pump

Voltage: 12 Volt (9.0 min – 16.0 vdc max)

Minimum Flow Rate: 28 gph, 106 liters per hour

Deadhead Pressure: 9.0 to 12.0 psi (62 to 83 kPa)

Maximum Current Draw: 2.3 amps

Inlet & Outlet Size: 1/8-27 NPSF

Operating Temperature Range: -40°F to 155°F (-40°C to 68.3°C)

Life: >8,000 hours (Diesel Fuel)

Dry Lift: 48 inches

Reverse Voltage Protected

Transient Voltage Protection: 100 volts

Compatible Fuels: No-lead regular gasoline, premium gasoline, gasoline-alcohol blends, diesel and biodiesel fuels (20% and 100%), and E85

Corrosion Resistance: 96 hr. salt spray test (ASTM B-117)

Inlet Filter Screen: 70 micron

Outlet Check Valve: Yes

Electrical Connector: Packard (Accepts mating connector 12015782)

Available Options:

Adjustable Pressure Regulator 135-631

The FRC series fuel pump is designed to supply fuel for internal combustion engine applications only. It is not intended or designed for continuous operation applications such as heater or stove systems.