



Guzzler® 24 VDC Electric Pump GE-0504D



Pictured with pressure gauge — not included

- 2.8 – 16.5 GPM
- Features 24 VDC motor with optional speeds from 20 – 120 RPM
- Accommodates 1-1/4" – 2" hose
- Large flange sizes suitable for sanitation applications

Specifications / Options

Body & Ports *	Delrin / Gray
Clamp Ring	Aluminum Motor Mounting Plate
Valves *	Flapper, Duckbill
Diaphragm *	Buna-N, Buna-N Double Sided, Neoprene, Viton, EPDM, Silicone
Clevis/Button Assembly *	SS Washer + Aluminum Clevis
Motor	24 VDC, 1/8 HP

* in contact with fluid

Available 24 VDC Motors & Performance

Pump Flow Rate ³ (GPM)	Motor Speed ³ (Name-plate RPM)	Full Load Torque (In-Lbs.)	Input HP	Full Load Amps	Max Pressure (psi)	Max Lift ⁴ (ft)	Max Head (ft)
2.8	20	254	1/8	4.5	15	20	25
4.1	30	254	1/8	5.3	15	20	25
8.8	64	113	1/8	5.3	8	18	18
16.5	120	60	1/8	5.3	4	9	9

³ at 0 lift, 0 head

⁴ Check valve recommended for lifts above 12 ft.

Performance

Flow Rate	per stroke: 0.55 Qt (0.52L)
Max Lift	20 ft (6.1 m) ^{1,2}
Max Head	25 ft (7.6 m) ¹
Max Pressure	15 psi (1.0 bar) ¹
Max Service Temp	150°F (66°C)

¹ depending on choice of motor

² with a check valve

Available Ports

	in	1-1/4	1-1/2	2
	cm	3.18	3.81	5.08
Hose (Smooth)			S	•
NPT Female (Tapped)		•		
NPT Male (Threaded)			•	

S Standard • Optional

Motor Specifications

Motor Type	24 VDC, Permanent Magnet
Enclosure	Total Enclosed Non-ventilated
Brushes	Externally replaceable
Rotation	Reversible
Ambient	40°C
Thermal Protection	None
Lubrication	Permanent Heavy Fluid Gear Oil
Gears	Hardened Steel
Weight	~12 lbs
Certifications	UL Recognized (E47479)

Valve Options

Flapper — General purpose liquid transfer.



Duckbill — For dirty liquid and sewage. Permits mounting in any position.



Installation Note: Pump cannot be mounted using pump body mounting feet alone. Motor needs additional support.



Optional motor support bracket. (Part # BR-01.)



Optional under-body support braces bottom of pump bowl for high pressure operation.

Guzzler® 24 VDC Electric Pump GE-0504D



Example: GE-0504D-011-48-8080-TL

- Guzzler Electric Pump
- Model style #0504D: Delrin Body, Opposite Side Ports
- No Variable Speed control option
- Buna-N Flapper Valves
- Buna Diaphragm
- SS Washer & Aluminum Clevis
- Motor Mounting Plate Clamp Ring
- Inlet: 1-1/2" Smooth
- Outlet: 1-1/2" Smooth
- 24 VDC 64 RPM Motor

Guzzler Product	
Option	Code
Electric Pump	GE

Style (Family)	
Option	Code
Delrin, Opp. Side Ports	0504D

Speed Control	
Option	Code
None	0

Valves	
Option	Code
Flapper (Buna-N)	1
Duckbill (Buna-N)	6

Diaphragm	
Option	Code
Buna Nitrile	1
Buna-N 3-Ply	2
Neoprene	3
Viton	4
EPDM	5
Silicone	7

GE - 0504D - 0 1 1 - 4 8 - 80 80 - TL

Clevis/Button Assembly	
Option	Code
SS Washer & Alum Clevis	4

Clamp Ring	
Option	Code
Motor Mounting Plate	8

Option	Code	
	Inlet	Outlet
1-1/4" NPT Tapped	71	71
1-1/2" Smooth	80	80
1-1/2" NPT Threaded	82	82
2" Smooth	90	90

24 VDC Motor		
Option (Speed / Torque)	Code	
20 rpm / 254 in-lbs	TA	
30 rpm / 254 in-lbs	TC	
64 rpm / 113 in-lbs	TL	
120 rpm / 60 in-lbs	TX	

